

TOOL FEATURES

1. Robust gravity-casted engine pneumatic piston return design.
2. Hardened clinch teeth for clinch consistency & tool longevity.
3. Ergonomic rubber handle grip.
 - All metal construction.
 - Pneumatic piston return minimizes cycle time.
 - 3 nose lengths available.
 - Adjustable for left or right handed operation.



HR7

25mm (1")

HR7E

40mm (1.6")

HR77XE

70mm (2.8")



FASTENER SPECS

| | |
|-------------------|--|
| Type | 15 GA. Bostitch RING15 / Meihotech GDH |
| Loading Capacity | 100 Rings |
| Ring Height | 12mm (1/2") |
| Crown Width | 23.9mm (15/16") |
| Wire Dia. | 1.8mm (0.07") |
| Open Ring Size | 19mm (3/4") |
| Closure Ring Size | 7.9~10.7mm (5/16"~27/64") |

TOOL SPECS

| | |
|--------------------|--|
| Weight | HR7 : 1.39 kgs (3.0 lbs) HR7E : 1.53 kgs (3.4 lbs) HR77XE : 1.72 kgs (3.8 lbs) |
| Height | 189mm (7.4") |
| Width | 89mm (3.5") |
| Length | HR7 : 335mm (13.2") HR7E : 354mm (13.9") HR77XE : 381mm (15") |
| Operating Pressure | 5.9~7.9 bar (85~115 psi) |
| Applications | Bag Closure, Bedding, Automotive Seating, Wire Cages, Fencing |

